



GLOBAL EAST ASIA TECHNOLOGY CO.,LIMITED

Product name: 1710-2700MHz MIMO Panel Antenna

Product model: GL-DY1727S46513

Applications:

2G/3G/WLAN/WIFI/LTE Network System

Features:

Multi-input and Multi-output Technology



Electrical Specifications	
Frequency Range-MHz	1710-2700
Polarization	$\pm 45^\circ$
VSWR	≤ 1.5
Gain-dBi	13
Horizontal beam width	65°
Vertical beam width	25°
Front-to-back ratio-dB	≥ 25
Isolation between ports-dB	≥ 30
Input Impedance- Ω	50
Maximum input power-W	50
Lightning protection	DC Ground
Mechanical Specifications	
Input connector type	4×7/16DIN Female
Connector place	Bottom
Dimensions-mm	200×160×80
Antenna weight-KGS	3.8
Radome material	UPVC
Radome color	Gray
Mechanical tilt	$0 \sim 12^\circ$
Operating temperature	-40°C to $+65^\circ\text{C}$
Rated Wind Velocity-m/s	60
Mounting hardware-mm	$\phi 35 \sim \phi 75$

Add: Room826, Floor 8,BLDG 13, University Science Park(East), Zhengzhou City, P.R.Henan, China.

Tel: 86-371-60911368 Email:info@global-antenna.com

Web:http://www.asialeren.com http://www.global-antenna.com