



GLOBAL EAST ASIA TECHNOLOGY CO.,LIMITED

Product name:617-960 / 1710-6000 MHz 3 / 5 dBi MIMO Omni Antenna

Product model: GL-L627FG4D



Electrical Specifications

Frequency Range (MHz)	617-960	1710-2700	3300-4700	5200-6000
Horizontal Half-power Beamwidth (°)	360	360	360	360
Vertical Half-power Beamwidth (°)	60	35	35	35
Gain (dBi)	3	5	4.5	4
Polarization	Vertical (2×)			
Typical VSWR	≤2.0			
Average Power, Maximum (W)	50			
Impedance (Ω)	50			

Mechanical Specifications

Dimensions (mm)	Φ63×360±10
Net Weight (kg)	1.5 (installation kit included)
Radome Material	UPVC
Radome Color	White
Cable Length (m)	5 (16ft)
Cable model number	3D-FB
Connector	SMA Male (2×)

Environmental Specifications

Application	Outdoor
Operating Temperature (°C)	-40 to +70 (-40 to 158°F)
Humidity (%)	5 to 95
Survival Wind Velocity (m/s)	60

Mounting Specifications

MOUNTING BRACKETS ARE INCLUDED UNLESS OTHERWISE SPECIFIED

Mounting Mast Diameter (mm)	Φ 40 to 50
-----------------------------	------------

Add: Room 826, Block B,BLDG 18, University Science Park(East), Zhengzhou City,P.R.Henan,China.

Tel: 86-371-60911368 Email:info@global-antenna.com

Web:<http://www.asialeren.com> <http://www.global-antenna.com>